

SoundSTOP

HIGH PERFORMANCE
ACOUSTIC FLOORING SYSTEM

WWW.ADVANCEDFLOORINGCC.COM

All products available in cushioned, standard glue down AND floating click plank flooring! Designed to cover all your floor covering needs.



SoundSTOP

HIGH PERFORMANCE ACOUSTIC FLOORING SYSTEM

What is SoundStop?

SoundStop is a high performance vinyl plank with a built in acoustical underlayment product designed to reduce the transmission of sound. SoundStop is designed with customization in mind, allowing you to select the precise thickness that meets your requirements.

What is SoundStop made of?

SoundStop is made using IXPE padding. IXPE is a premium acoustical underlayment made with ultra fine, high density, closed-cell & cross-linked technology, ensuring maximum sound reduction.

SoundStop can be applied to:

- Multi-Family
- Condominiums
- College Dorms
- Classrooms
- Office Buildings
- Hospitals
- Any area where sound reduction is desired



SoundSTOP

HIGH PERFORMANCE ACOUSTIC FLOORING SYSTEM

SoundStop I

Size: 7" x 48"

Thickness: 3mm

Wear Layer: 6-mil, 8-mil, 12-mil

Pad: IXPE

Finish: DiamondGuard™ / HealthGuard™

Pieces per carton: 16

Sf per carton: 48

Sf per pallet: 2160

MOQ: Contact your sales representative

SoundStop II

Size: 7" x 48"

Thickness: 3.5mm

Wear Layer: 12-mil, 20-Mil

Pad: IXPE

Finish: DiamondGuard™ / HealthGuard™

Pieces per carton: 19

Sf per carton: 44.36

Sf per pallet: 2439.8

MOQ: Contact your sales representative

SoundStop III

Size: 9"x60" (Custom sizes available)

Thickness: 4.0 mm

Wear Layer: 20 mil

Pad: IXPE

Finish: DiamondGuard™ / HealthGuard™

Pieces per carton: 13

Sf per carton: 49

Sf per pallet: 2156

MOQ: Contact your sales representative

SoundStop IV

Size: 7" x 48" or 9" x 60" (Custom sizes available)

Thickness: 5mm

Wear Layer: 20-mil

Pad: IXPE

Wear Layer: ASK

Finish: DiamondGuard™ / HealthGuard™

ASTM SPECIFICATIONS / IIC STC RATINGS

Tested without a soundmat: STC61, IIC56, HIIC68

Tested with a 1/8" Soundmat: STC60, IIC58, HIIC65

Tested with a 1/4" Soundmat: STC60, IIC59, HIIC70

Tested on 6" of Concrete with a drop ceiling: STC62, IIC64

Meets these standards: ISO 24342:2018, ISO 24346:2006, ISO 23997:2007, ISO 23999:2021, ISO 24344:2008, Method A, ISO 4918:2016/Amd.1:2018, ISO 105-B02:2014, ASTM F1515-21, EN ISO, 10582:2018 (ISO 10582:2017) Annex B, EN 16094:2021, Procedure B, EN ISO 10582:2018, (ISO 10582:2017)

Recommended Adhesive: SAR5000 Pressure Sensitive Adhesive

see website for specifications

*All products are also available with our Waterproof TriCore™ patented
Unilin Floating Click*

Contact your sales representative for more information

1-512-503-2106

SoundSTOP I & II

200 Sandy Oak



201 Beach Wood



202 Bronze Wood



204 Brushed Earth



205 Copper Oak



206 Vermont Maple



300 Centurion



301 Silvius



302 Vulcan



303 Pollux



304 Remus



305 Ambrosius



306 Natural Oak



307 Taupe Wood



308 Barnwood



SoundSTOP III

500 Pintail



501 Shaka



502 Hang Ten



504 Carve



505 Kahuna



506 Wahine



510 Offshore



511 Tidal



600 Smoked Hickory



601 Lumber Legends



602 Grain & Glory



603 Chisel & Charm



604 Timber Traditions



605 Forest Forge

