



Innovato Collection Acoustical SPC Click

5mm thickness: (Includes a 1mm Hi Mesh EVA Acoustical Pad)

Ph: (512) 861-1952

Website: www.advancedflooringc.com

5mm Soundstop Acoustical Click-(Includes 1mm IXPE Pad)

Size: 9"x48", 7.25"x48", 6"x36"

Wear Layer: 8-mil, 12-mil, 20-mil

Texture: Deep Embossed


Thickness: 5mm-(Includes a 1mm IXPE Underlayment)

Description	Results
ASTMF1700 -(ASTMF2055, ASTMF386, ASTMF410, ASTMF2055, ASTMF1914, ASTMF137, ASTMF2199, ASTMF925, ASTMF2199, ASTMF1515, ASTMF1514, Certificate of Compliance	Pass
ANSIA.137 Dynamic Co-efficient of Friction	Average DCOF .44
ASTME648 Critical Radiant Flux of Floor Covering Systems	Meets or exceeds Class 1 rating as specified in NFPA Life Safety Code 101 and IBC 804.2 Classification
ASTME662 Smoke Density	This sample passes the requirements of 450 or less
ASTMF137 Flexibility of Resilient Flooring Materials	Passes 6mm Mandrel
ASTMF925-Resistant to Chemicals	Pass
ASTMF1514 Measuring Heat Stability-(7 Days)	Test requirements of < 8.0 Delta E were met by the tested samples
ASTMF1515-Measuring Light Stability of Flooring by color change	Test requirements of < 8.0 Delta E were met by the tested samples
ASTMF1914-(Short Term Indentation)	Residual Indentation at 40 lbs-0.015 Inch (7.78%)
ASTMF2199-(Dimensional Stability after exposure to heat)	Length--0.008 Inch per 12 inches (-0.07%) Width-0.013 Inch per 12 inches (-0.11%)
ASTMF2055-(Size, Tolerance)	.016 in/lin ft
ASTMF410-Thickness/Wear Layer	Requirement: Commercial .02, Test Result: .011 inch/.26mm
Certificate of Compliance	Requirement: Max 1/3 of flat surface area/Test Result: Pass
ASTM E90&492 Acoustical Tests	STC61, IIC54, HIIC63

Soundstop LVT Acoustical SPC Click

Sizes & Systems

Thickness	Sq Ft Per Carton	Boxes Per Pallet	Sq Ft Per Pallet	Sq Ft Per Container	Pallets Per Container
5mm SPC Click (Includes a 1mm IXPE Acoustical Underlayment)	24	48	1152	23039	20



Amazing Cherry



Breezy Oak



Brookside Oak



Natural White Oak




Bootshake Oak




Butterscotch Oak



Crystal Oak



Opera House Oak




Glazed Hickory



Catalina Grey



Forest Dark



Stadium Oak

Built-In Acoustical
Underlayment

ASTM Acoustical Results

- STC61
- IIC54
- HIIC63

***Tested on a Wood
Floor Assembly**

