

## **Venti-Luxe XL Data Sheet**

## **PRODUCT SPECIFICATIONS**

Size 9"x60" 5.5 mm

Thickness 20 mil

Wear Layer ArmourGuard Microbead Technology

Finish QuietStep Cushion +

Attached Pad TriCore ESPC

Core Yes

Micro Beveled Edge Light Commercial

Traffic Use Floating Click

Installation7Pieces Per Carton27SF Per Carton60Cartons Per Pallet1,575

SF Per Pallet

## WARRANTY

15 Year Light Commercial / Limited Residential Lifetime

## **PERFORMANCE**

ASTM F2055 Size **Pass Pass** ASTM F386 Thickness **ASTM F2055 Squareness Pass** ASTM F1914 Residual Indentation Pass **Pass** ASTM F137 Flexibility ASTM F2199 Dimensional Stability **Pass Pass ASTM F925 Chemical Resistance** ASTM F1514 Resistance to Heat **Pass** ASTM F1515 Resistance to Light **Pass** ASTM F 970 Static Load Limit **Pass** 

Certified Low Emitting Product Meets Guidelines
Indoor Air Quality Meets Guidelines

Indoor Sound Transmission Test IIC: 68 (test condition: 6"concrete slab with drop ceiling)

(512) 861-1952

